


## General Hardware

### HEX HEAD CAP SCREW (HHCS)




Part Number	Thread Size	Length
HHCS037075	3/8"	3/4"
HHCS037100	3/8"	1"
HHCS037125	3/8"	1 1/4"
HHCS037150	3/8"	1 1/2"
HHCS050094	1/2"	15/16"
HHCS050119	1/2"	1 3/16"
HHCS050150	1/2"	1 1/2"

#### Material / Finish Specifications

**Material:** SAE J429 GR 2

**Finish:** ASTM B633 Type III SC1 (EG)

### STEEL THREADED ROD (HTHR)



Part Number	Thread Size
HTHR037	3/8"
HTHR050	1/2"
HTHR062	5/8"


#### Material / Finish Specifications

**Material:** ASTM A36 or F1554 GR 36 minimum

**Finish:** ASTM B633 Type III SC1 (EG)

**Yield Strength:** 36,000 psi minimum

### HEX NUTS (HHXN)



Part Number	Thread Size
HHXN037	3/8"
HHXN050	1/2"
HHXN062	5/8"


#### Material / Finish Specifications

**Material:** ASTM A563, Grade A

**Finish:** ASTM B633 Type III SC1 (EG)

Dimensions in accordance with ANSI B18.2.2

### STEEL COUPLER NUTS (HRCN)



Part Number	Thread Size	Length
HRCN037	3/8"	1 3/4"
HRCN050	1/2"	1 3/4"
HRCN062	5/8"	2 1/8"

#### Material / Finish Specifications

**Material:** ASTM A563, Grade A

**Finish:** ASTM B633 Type III SC1 (EG)

**Atkore**<sup>™</sup>  
**Unistrut**

16100 S. Lathrop Ave  
Harvey, IL 60426  
Toll-Free: (800) 882-5543

[www.unistrutseismic.com](http://www.unistrutseismic.com)

Structural Engineer: Rami Elhassan  
California SE No. 3930

Page:

**6c.1**